

Cinelex SKYNODE

USB-powered wireless DMX receiver, designed for effortless integration with ARRI SkyPanel

ARRI SkyPanel COMPATIBLE

Effortless integration with ARRI SkyPanel, adding wireless DMX in a simple plug & play manner.

INTELLIGENT SYNCING

Quick & easy setup using LumenRadio protocol. Sync transmitter with one or multiple SKYNODE's.

USB POWERED

SKYNODE draws its power from any 5V USB source, including the USB-A port on ARRI's SkyPanel.



COMPACT DESIGN

SKYNODE is miraculously compact, the largest component being its 5-pin XLR connector.

PROFESSIONAL READY

Robust construction - built to withstand tough rental & on-set environments.

STANDARDS COMPLIANT

All Cinelex products meet international regulatory standards including FCC, CE & RohS.

Cinelex SKYNODE

USB-powered wireless DMX receiver, designed for effortless integration with ARRI SkyPanel

Specification

Wireless Protocol

Protocol	LumenRadio
Operational Frequency	2.4GHz (2402-2480MHz)
Range	Up to 100m (environment dependent)
DMX	DMX512, DMX512 (1990) & DMX512-A

Power

Micro-USB	5V
Power Consumption	1W

Controls

1x "SYNC" Button	Synchronise SKYNODE with Transmitter
------------------	--------------------------------------

Connectors

- 1x DMX XLR 5-Pin Male
- 1x Micro-USB Power Input Female
- 1x Built-In Antennae

LED Indicators

1x "STATUS" LED	Connection Status
1x "POW" LED	Power Input Confirmation
3x Signal Strength LEDs	Signal Strength Indicator

Size (with Antennae)

Weight	50g
Dimensions	60mm x 25mm x 40mm (L x W x D)